

Quality Management ISO 9001 Code: TD_EGGER_Silenzio_Duo_EN

> Revision: 02

Date: 18.11.2020

Technical data sheet

EGGER Silenzio Duo

Application area
Underlay material for floating flooring installation of laminate flooring elements (EN13329) and MMF flooring (EN 16511:2014) on mineral sub floors.



Product	Silenzio Duo
Material	XPSHD + met. PET
Color	gold-anthracite
Type of delivery	Folding mat
Packaging	10 m² / package / 42 packages / pallet
Accreditations /Certificates /Declarations	Building Inspectorate Approval TÜV toxproof, A+ (Èmissionsdans l'air intérieur)

Material data

Parameter	Specification	Tolerance	Test method
Thickness [mm]	1,5	± 15%	EN 823:2013
Length [m]	8,5	+5% / -1%	EN 823:2013
Width [m]	1,18	+2,5% / -1%	EN 823:2013
Reaction to fire	Efl	-	EN 13501-1:2010
Water absorption [%]	≤ 1	-	EN 12087
Thermal resistance Rλ [m²K/W]	~ 0,04	-	EN 12664:2002
Water vapor diffusion resistance SD [m]	>150	-	EN 12086:2013

Technical data concerning CEN TS 16354

Description	Parameter	Value	Recommendations according to the EPLF
Impact Sound Reduction	IS [dB]	19	> 18
Reflected Walking Sound Reduction	RWS [%]	38 according to IHD –W431	in progress
Resistance to Large Ball	RLB [mm]	≤ 1500	≥ 1.200
Compressive Strength	CS [kPa]	400	≥ 60
Compressive Creep	CC [kPa]	-	≥ 20
Dynamic Load	DL [cycles]	> 400.000	≥ 100.000
Punctual Conformability	PC [mm]	≤ 1	≥ 0.5

MORE FROM WOOD.



Information: All above mentioned values were determined under laboratory conditions and defined laboratory materials and structures and may with different system flooring components deviate from these test values. For all of they mentioned performance values inaccuracies are possible owing to the testing methods.

The information given above is based on our current state of knowledge and should be used for information of our product application. This should not be taken to as an assurance of certain quality of our products or their use for specific purposes. Subject to change, legal obligations cannot be derived from the information in this document. Existing commercial protective rights are to be observed.