


## Technický prospekt

### Podkladové materiály pre Laminátové podlahy EGGER



Požiadavky na zníženie krokového hluku pri hrúbke od 1.5 do 3.0 mm a odporúčaná hodnota odolnosti proti stlačeniu CS  $\geq$  60 kPa, alebo aspoň CS  $\geq$  10 kPa

### Vhodný/ schválený podkladový materiál

Výrobca/ Distribútor	Podkladový materiál	Hrúbka [mm]	CLIC fit!		UNI fit! Patented	
EGGER	Silenzio Easy	2,0	✓	✓	✓	✓
EGGER	Silenzio Easy SD	2,0	✓	✓	✓	✓
EGGER	Silenzio DUO	1,5	✓	✓	✓	✓
EGGER	Silenzio Cork	2,0	✓	✓	✓	✓
Selit	Selitbloc	1,5	✓	✓	✓	✓
Selit	Ökolit - Kork	2,0	✓	✓	✓	✓
Selit	Selit-Pro Aqua Stop	2,0	✓	✓	✓	✓
Selit	Selitac	2,2	✓	✓	✓	✓
Selit	Selitac	5,0	✓	✗	✓	✗
Selit	Selitac Aqua Stop	5,0	✓	✗	✓	✗
Selit	Axton - laminate combi underlay	2,0	✓	✓	✓	✓
Sekisui Alveo	ALVEO Professional 140	1,5	✓	✓	✓	✓
Sekisui Alveo	ALVEO PRO+	2,0	✓	✓	✓	✓
Sekisui Alveo	SOUNDPROTECT+ ultra	2,0	✓	✓	✓	✓
Sekisui Alveo	ALVEO Professional Maximum	2,0	✓	✓	✓	✓
Ewifoam	Vinlic Professional PU	1,6	✓	✓	✓	✓
Ewifoam	Vinlay Professional SK	2,1	✓	✓	✓	✓
Ewifoam	Duogard Maxima	2,0	✓	✓	✓	✓
Ewifoam	Duogard Maxima Aquastop	2,0	✓	✓	✓	✓
Ewifoam	Silenzia Standard	2,0	✓	✗	✓	✗
Ewifoam	Silenzia Classic	3,0	✓	✗	✓	✗
Ewifoam	Silenzia Classic Aquastop Smart	3,0	✓	✗	✓	✗
Ewifoam	Universol 1000	1,5	✓	✓	✓	✓
Ewifoam	Universol Alu classic	2,6	✓	✓	✓	✓
Ewifoam	Polytex Aquastop Smart	1,6	✓	✗	✗	✗
Ewifoam	Duogard Professional	2,2	✓	✓	✓	✓
Ewifoam	Duogard strong	2,0	✓	✓	✓	✓
PCI Thomsit	Thomsit TF302	2,0	✓	✓	✓	✓
PCI Thomsit	Thomsit TF303	3,0	✓	✓	✓	✓

Výrobca/ Distribútor	Podkladový materiál	Hrúbka [mm]	CLIC fit!		UNI fit! Patented	
Arbiton	Secura	3,0	✓	✗	✓	✗
WPT	SRL Solid Viscious Gummimatte	1,7	✓	✓	✓	✓
WPT	Natural Sound Basic SD PU mit Alubeschichtung	2,2	✓	✓	✓	✓
WPT	Natural Sound Comfort SD PU mit Alubeschichtung	3,0	✓	✓	✓	✓
Pregis	LBPE Black + PEE	1,3	✓	✓	✓	✓
Steico	Holzfaserdämmplatte	2,5	✓	✗	✓	✗
Dinamik-Izmir	Dyna Foam	3,0	✓	✓	✓	✓
Stiroleks	Stiroleks XPS	3,0	✓	✓	✓	✓
Ebeco	Ebisol	3,0	✓	✗	✓	✗
Taiga	Soundblocker Foam	3,0	✓	✓	✓	✓
Nostra	Nostrasonic Alu EVA mit ALU PET	3,0	✓	✗	✓	✗
Nostra	Nostrasonic Alu EVA mit ALU PET	2,0	✓	✗	✓	✗
Wallmann	No Noise ( Warm, silent and stable)	3,0	✓	✗	✓	✗
Kraiburg Relatec	Damtec® Standard	3,0	✓	✓	✓	✓
Südafrika	Whisper LAY - beschichtete Gummimatte	2,0	✓	✓	✓	✓
Parquet Directo	Eva Gold Lamina	2,0	✓	✓	✓	✓
Maxeda (Mac Lean)	Sencys Faltmatte grau	3,0	✓	✓	✓	✓
Maxeda (Mac Lean)	Sencys isotac	5,0	✓	✗	✓	✗
MCD	Indicoustic sol	2,0	✓	✗	✓	✗
MCD	Indicoustic sol PV Plus	3,0	✓	✗	✓	✗
MSD	Indicoustic sol PV Ultra	2,0	✓	✓	✓	✓
Amorin	Rollenkork	2,0	✓	✓	✓	✓
Winoe/ Windmöller	Sound Protect Eco SD	2,0	✓	✓	✓	✓
Repac/ 4 Floor	Acoustic Board	1,8	✓	✓	✓	✓
Repac/ 4 Floor	Acoustic Tech	1,3	✓	✓	✓	✓
Repac/ 4 Floor	Acoustic LVT	1,0	✓	✓	✓	✓
Repac/ 4 Floor	XPS Rolle	2,0	✓	✓	✓	✓
Repac/ 4 Floor	Rollenkork	2,0	✓	✓	✓	✓
Austrotherm	PE 2/200 Schwerschäum	2,2	✓	✓	✓	✓
Repac	XPS Platte grau	3,0	✓	✓	✓	✓
Opti- Acoustics Step	Sealed Air Opti-Step 3000	1,2	✓	✓	✓	✓
CMS Danskín Acoustic	Requpol 4515 Multi	3,0	✓	✓	✓	✓

**Poznámka:**

Tento technický list je starostlivo vypracovaný podľa našich najlepších znalostí. Je určený len na informačné účely a nepredstavuje záruku z hľadiska vlastností výrobku alebo jeho vhodnosti pre špecifické aplikácie. Vychádza z praktických skúseností, našich vlastných testov a zodpovedá nášmu súčasnému stavu vedomostí. Za akékoľvek chyby, chyby v normách alebo chyby tlače neručíme. Navyše technické zmeny môžu vyplývať z neustáleho vývoja podlahy EGGER, ako aj zo zmien noriem a dokumentov verejného práva. Preto obsah týchto pokynov na spracovanie nemôže slúžiť ako návod na použitie ani ako právne záväzný základ.

